NSN 5970-01-110-3770

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-110-3770

| Tempurature Rating: |
|--|
| -55.0 degrees celsius |
| Environmental Protection: |
| Flame resistant and mildew resistant and solvent resistant and water resistant |
| Main Body Wall Thickness: |
| 0.070 inches after unrestricted recovery |
| Main Bodylength: |
| 2.920 inches after unrestricted recovery |
| Main Body Small End Inside Diameter: |
| 0.220 inches as supplied |
| Main Body Large End Inside Diameter: |
| 1.030 inches as supplied |
| Distance From Bottom Of Shoulder To Large End Of Main Body: |
| 0.480 inches after unrestricted recovery |
| Min. Tensile Strength (psi): |
| 1800 pounds per square inch |
| Special Features: |
| Large end has lip; wall thk tapers from large end of main body to 0.045 in. After recovery small end; molding ports included |
| Flexibility: |
| Flexible |
| Color: |
| Black |
| Material: |
| Rubber, synthetic, mil-r-46846, ty iii, class 2 or rubber, viton rt-1312, raychem corp |
| Material: |
| Rubber, synthetic, mil-r-46846, ty iii, class 2 or rubber, viton rt-1312, raychem corp |
| Style Designator: |
| Boot-straight-long |
| Dielectric Material Voltage Rating Per Unit Thickness: |
| 200.0 volts per military /0.001 inch/ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A22500 |
| |