Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-110-7613

Tempurature Rating:
-55.0 degrees celsius and 135.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and water resistant
Large End Wall Thickness Of Main Body:
0.080 inches after unrestricted recovery
Small End Wall Thickness Of Main Body:
0.045 inches after unrestricted recovery
Main Bodylength:
8.410 inches after unrestricted recovery
Main Body Small End Inside Diameter:
1.720 inches as supplied
Main Body Large End Inside Diameter:
1.720 inches as supplied
Distance From Top Of Shoulder To Small End Of Main Body:
6.720 inches after unrestricted recovery
End Largest Diameter:
1.690 inches after unrestricted recovery
Min. Tensile Strength (psi):
1500 pounds per square inch
Lip Height:
0.120 inches after unrestricted recovery
Lip Width:
0.065 inches after unrestricted recovery
Special Features:
White color stripe; includes drain holes; inside adhesive coated
Flexibility:
Semirigid
Height:
1.080 inches after unrestricted recovery
Color:
Black
Material:
Plastic, polyolefin, mil-i-81765/1, typei
Material:
Plastic, polyolefin, mil-i-81765/1, typei
Style Designator:
Boot-90 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500