NSN 5970-01-110-7614

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-110-7614

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Large End Wall Thickness Of Main Body:

0.100 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.055 inches after unrestricted recovery

Main Bodylength:

5.250 inches after unrestricted recovery

Main Body Small End Inside Diameter:

2.470 inches as supplied

Main Body Large End Inside Diameter:

2.310 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

2.920 inches after unrestricted recovery

End Largest Diameter:

2.090 inches after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Lip Height:

0.120 inches after unrestricted recovery

Lip Width:

0.080 inches after unrestricted recovery

Special Features:

Port holes included

Flexibility:

Flexible

Height:

1.310 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin, mil-i-81765/1, ty ii or plastic, polyolefin, rt-1304, raychem corp

Material:

Plastic, polyolefin, mil-i-81765/1, ty ii or plastic, polyolefin, rt-1304, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

NSN 5970-01-110-7614

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A22500