Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-111-3683

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Coating Material:

Adhesive

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Main Body Wall Thickness:

0.080 inches after unrestricted recovery

Main Bodylength:

7.000 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.470 inches as supplied

Main Body Large End Inside Diameter:

1.470 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

0.550 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

White color stripe; large end has lip; small end wall thk 0.045 in. Nom after unrestricted recovery; adhesive coated inside surface; includes

0.120 in. Diameter drain holes

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, mil-i-81765/1, type i

Material:

Plastic, polyolefin, mil-i-81765/1, type i

Style Designator:

Boot-straight-long

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500