Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-111-3684

view Online at https://aerobasegroup.com/nsn/5970-01-111-3064	
Reliability Indicator:	
Not established	
Tempurature Rating:	
-55.0 degrees celsius and 135.0 degrees celsius	
Environmental Protection:	
Corrosion resistant and flame resistant and mildew resistant and water resistant	
Main Body Wall Thickness:	
0.080 inches after unrestricted recovery	
Main Bodylength:	
3.000 inches after unrestricted recovery	
lain Body Small End Inside Diameter:	
1.720 inches as supplied	
Main Body Large End Inside Diameter:	
.720 inches as supplied	
Distance From Bottom Of Shoulder To Large End Of Main Body:	
0.600 inches after unrestricted recovery	
/in. Tensile Strength (psi):	
500 pounds per square inch	
Special Features:	
White color stripe; four 0.120 in diameter drain holes; large end has lip; small end wall thk 0.045 in after unrestricted rec	overy; adhesive
coated inside surface	
lexibility:	
Semirigid	
Color:	
Black	
Material:	
Plastic, polyolefin, mil-i-81765/1, type i	
laterial:	
Plastic, polyolefin, mil-i-81765/1, type i	
Style Designator:	
Boot-straight-long	
Dielectric Material Voltage Rating Per Unit Thickness:	
200.0 volts per military /0.001 inch/	
Shelf Life:	
N/a	
Jnit Of Measure:	
_	
Demilitarization:	
No	
Fiig:	
A22500	