Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-117-0787

| Reliability Indicator:                   |                   |  |  |
|------------------------------------------|-------------------|--|--|
| Not established                          |                   |  |  |
| Overall Length:                          |                   |  |  |
| Any acceptable                           |                   |  |  |
| Tempurature Rating:                      |                   |  |  |
| -75.0 degrees celsius and 120.0 degre    | es celsius        |  |  |
| Environmental Protection:                |                   |  |  |
| Corrosion resistant and mildew resistant | nt                |  |  |
| Expanded Inside Diameter:                |                   |  |  |
| 0.375 inches                             |                   |  |  |
| Recovered Inside Diameter:               |                   |  |  |
| 0.187 inches                             |                   |  |  |
| Recovered Wall Thickness:                |                   |  |  |
| 0.040 inches                             |                   |  |  |
| Heat Shrinkage Rating In Percent:        |                   |  |  |
| 50.0                                     |                   |  |  |
| Min. Tensile Strength (psi):             |                   |  |  |
| 1700 pounds per square inch              |                   |  |  |
| Flexibility:                             |                   |  |  |
| Flexible                                 |                   |  |  |
| Color:                                   |                   |  |  |
| Black                                    |                   |  |  |
| Material:                                |                   |  |  |
| Plastic, polyolefin, mil-i-23053/16      |                   |  |  |
| Material:                                |                   |  |  |
| Plastic polyolefin                       |                   |  |  |
| Style Designator:                        |                   |  |  |
| Shrinkable                               |                   |  |  |
| Dielectric Material Voltage Rating Pe    | r Unit Thickness: |  |  |
| 300.0 volts per military /0.001 inch/    |                   |  |  |
| Shelf Life:                              |                   |  |  |
| N/a                                      |                   |  |  |
| Unit Of Measure:                         |                   |  |  |
|                                          |                   |  |  |
| Demilitarization:                        |                   |  |  |
| No                                       |                   |  |  |
| Fiig:                                    |                   |  |  |
| A22500                                   |                   |  |  |
|                                          |                   |  |  |