AeroBase Group

View Online at https://aerobasegroup.com/nsn/5970-01-121-8671

view Online at https://aerobasegroup.com/hsn/5970-01-121-6671
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Large End Wall Thickness Of Main Body:
0.080 inches after unrestricted recovery
Small End Wall Thickness Of Main Body:
0.045 inches after unrestricted recovery
Main Bodylength:
4.250 inches after unrestricted recovery
Main Body Small End Inside Diameter:
1.470 inches as supplied
Main Body Large End Inside Diameter:
1.470 inches as supplied
Distance From Top Of Shoulder To Small End Of Main Body:
2.620 inches after unrestricted recovery
End Largest Diameter:
1.320 inches after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Lip Height:
0.120 inches after unrestricted recovery
Lip Width:
0.065 inches after unrestricted recovery
Special Features:
Port holes included
Flexibility:
Flexible
Height:
0.960 inches after unrestricted recovery
Color:
Black
Material:
Plastic, polyolefin, mil-i-81765/1, type 2 or plastic, polyolefin, rt1304, raychem corp
Material:
Plastic, polyolefin, mil-i-81765/1, type 2 or plastic, polyolefin, rt1304, raychem corp
Style Designator:
Boot-90 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A22500