Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-121-8672

Tempura	ature Rating:
-55.0 deg	grees celsius
Environ	mental Protection:
Corrosio	n resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Bo	dy Wall Thickness:
0.100 inc	ches after unrestricted recovery
Main Bo	dylength:
4.750 inc	ches after unrestricted recovery
Main Bo	dy Small End Inside Diameter:
2.470 inc	ches as supplied
Main Bo	dy Large End Inside Diameter:
2.470 inc	ches as supplied
Distance	e From Bottom Of Shoulder To Large End Of Main Body:
0.630 inc	shes after unrestricted recovery
Min. Ten	sile Strength (psi):
1200 pou	unds per square inch
Special	Features:
Large en	d has lip; small end has wall thk of 0.055 in. After recovery; includes two molding ports
Flexibilit	ty:
Flexible	
Color:	
Black	
Material	:
Plastic, p	oolyolefin, mil-i-81765/1, type 2 or plastic, polyolefin, rt1304, raychem corp
Material	:
Plastic, p	oolyolefin, mil-i-81765/1, type 2 or plastic, polyolefin, rt1304, raychem corp
Style De	signator:
Boot-stra	aight-long
Shelf Lif	e:
N/a	
Unit Of I	Measure:
Demilita	rization:
No	
Fiig:	