Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-123-0279

Reliability Indicate	ח:
Not established	
Tempurature Ratii	ng:
	us and 135.0 degrees celsius
Environmental Pro	otection:
Corrosion resistant	and flame resistant and mildew resistant and water resistant
Main Body Wall TI	nickness:
0.060 inches after	unrestricted recovery
Main Bodylength:	
4.170 inches after	unrestricted recovery
Main Body Small I	End Inside Diameter:
0.880 inches as su	pplied
Main Body Large	End Inside Diameter:
0.880 inches as su	pplied
Distance From Bo	ttom Of Shoulder To Large End Of Main Body:
0.460 inches after	unrestricted recovery
Min. Tensile Stren	gth (psi):
1500 pounds per so	quare inch
Special Features:	
Adhesive coated in	side surface; large end has lip; small end wall thk 0.045 in. Nom after unrestricted recovery; white color stripes
Flexibility:	
Semirigid	
Color:	
Black	
Material:	
Plastic, polyolefin, i	nil-i-81765/1, type i
Material:	
Plastic, polyolefin, r	nil-i-81765/1, type i
Style Designator:	
Boot-straight-long	
Dielectric Materia	Voltage Rating Per Unit Thickness:
200.0 volts per milit	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
3-	