Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-127-5157

## **Tempurature Rating:** -55.0 degrees celsius and 135.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Large End Wall Thickness Of Main Body: 0.060 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.060 inches after unrestricted recovery **Distance From Intersecting Centerlines To Edge Of Small End:** 1.750 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.500 inches as supplied Main Body Large End Inside Diameter: 1.500 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 0.420 inches after unrestricted recovery Angle Between Large End And Small End Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Large end has lip Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A22500