NSN 5970-01-129-4627

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-129-4627

Tom	nuratur	e Rating:
ı em	puratur	e Kating:

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Main Body Wall Thickness:

0.160 inches after unrestricted recovery

Main Bodylength:

6.500 inches after unrestricted recovery

Main Body Small End Inside Diameter:

2.600 inches as supplied

Main Body Large End Inside Diameter:

2.600 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

3.310 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

1.900 inches after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Special Features:

Large end has lip in 3 places; molding ports included

Flexibility:

Flexible

Color: Black

Material:

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mil-i-81765/1, type 2

Material:

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mil-i-81765/1, type 2

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500