Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-129-4630

view entitie at https://doi/babegroup.com/net/correction/125/1000
Tempurature Rating:
-55.0 degrees celsius and 135.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and water resistant
Main Body Wall Thickness:
0.130 inches after unrestricted recovery
Main Bodylength:
3.530 inches after unrestricted recovery
Main Body Small End Inside Diameter:
2.040 inches as supplied
Main Body Large End Inside Diameter:
2.040 inches as supplied
Distance From Bottom Of Shoulder To Large End Of Main Body:
0.940 inches after unrestricted recovery
Distance From Top Of Shoulder To Small End Of Main Body:
1.560 inches after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Special Features:
Large end has lip; molding ports included
Flexibility:
Flexible
Color:
Black
Material:
Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mil-i-81765/1, type 2
Material:
Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mil-i-81765/1, type 2
Style Designator:
Boot-straight
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A22500