Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-129-5603

Reliability Indicator:	
Not established	
Overall Length:	
Any acceptable	
Tempurature Rating:	
-25.0 degrees celsius and 125.0 degrees celsius	
Environmental Protection:	
Corrosion resistant and flame resistant and mildew resistant and water resista	ant
Expanded Inside Diameter:	
0.500 inches	
Recovered Inside Diameter:	
0.250 inches	
Recovered Wall Thickness:	
0.025 inches	
Heat Shrinkage Rating In Percent:	
50.0	
End Application:	
Mrap - cougar; mrap - m-atv dv178; mrap - cougar cat1 a2	
Min. Tensile Strength (psi):	
1500 pounds per square inch	
Special Features:	
Material: plastic, polyolefin, mil-dtl-23053/5, class 3	
Flexibility:	
Flexible	
Color:	
Black	
Material:	
Plastic, polyolefin, mil-dtl-23053/5, class 3	
Style Designator:	
Shrinkable	
Dielectric Material Voltage Rating Per Unit Thickness:	
500.0 volts per military /0.001 inch/	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Filg:	
A22500	