NSN 5970-01-130-1900

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-130-1900

_				_		
Т	am	niii	ratii	ro R	≀atin	u.
	CIII	vui	atu	161	\auii	ч.

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Main Body Wall Thickness:

0.160 inches after unrestricted recovery

Main Bodylength:

4.760 inches after unrestricted recovery

Main Body Small End Inside Diameter:

3.220 inches as supplied

Main Body Large End Inside Diameter:

3.220 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

1.510 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

1.880 inches after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Special Features:

Large end has lip; molding ports included

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mil-i-81765/1 type 1

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mil-i-81765/1 type 1

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500