Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-132-2838

Nc	ot established
0١	verall Length:
An	ny acceptable
Те	empurature Rating:
-25	5.0 degrees celsius and 125.0 degrees celsius
En	vironmental Protection:
Сс	prrosion resistant and flame resistant and mildew resistant and water resistant
Ex	panded Inside Diameter:
0.7	750 inches
Re	ecovered Inside Diameter:
0.3	375 inches
Re	ecovered Wall Thickness:
Be	tween 0.027 inches and 0.033 inches
He	eat Shrinkage Rating In Percent:
50	.0
En	nd Application:
Mr	ap - m-atv dv178; mrap - cougar cat1 a2
Mi	n. Tensile Strength (psi):
15	00 pounds per square inch
Sp	pecial Features:
Pla	astic, polyolefin, mil-dtl-23053/5, class 3
Fle	exibility:
Fle	exible
Co	blor:
Bla	ack
Ма	aterial:
Pla	astic, polyolefin, mil-dtl-23053/5, class 3
St	yle Designator:
Sh	nrinkable
Di	electric Material Voltage Rating Per Unit Thickness:
50	0.0 volts per military /0.001 inch/
Sh	nelf Life:
N/a	a
Ur	nit Of Measure:
De	emilitarization:
Nc	
Fii	ig:
A2	22500