NSN 5970-01-147-7209

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-147-7209

_				_		
Т	am	niii	ratii	ro R	≀atin	u.
	CIII	vui	atu	161	\auii	ч.

-55.0 degrees celsius and 125.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant and water resistant

Main Body Wall Thickness:

0.070 inches after unrestricted recovery

Main Bodylength:

1.500 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.920 inches as supplied

Main Body Large End Inside Diameter:

0.920 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

0.830 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

0.400 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Molding ports included; inside adhesive coated; large end has lip and circular ridge inside

Flexibility:

Semirigid

Color: Black

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500