

View Online at <https://aerobasegroup.com/nsn/5970-01-149-4187>

**Tempurature Rating:**

-55.0 degrees celsius and 125.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

**Distance From Centerline Of Main Body To End Of First Branch:**

Any acceptable as supplied

**Main Body Inside Diameter:**

0.520 inches as supplied

**First Branch Inside Diameter:**

0.760 inches as supplied

**Main Body Wall Thickness:**

0.040 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.040 inches after unrestricted recovery

**Main Bodylength:**

1.500 inches after unrestricted recovery

**Angle Between Main Body And First Branch Centerlines In Deg:**

90.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1200 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpf-666, high voltage engineering corp

**Material:**

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpf-666, high voltage engineering corp

**Style Designator:**

Transition-cross-shaped

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500