NSN 5970-01-149-4187

Fiig: A22500

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-149-4187
Tempurature Rating:
-55.0 degrees celsius and 125.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Distance From Centerline Of Main Body To End Of First Branch:
Any acceptable as supplied
Main Body Inside Diameter:
0.520 inches as supplied
First Branch Inside Diameter:
0.760 inches as supplied
Main Body Wall Thickness:
0.040 inches after unrestricted recovery
First Branch Wall Thickness:
0.040 inches after unrestricted recovery
Main Bodylength:
1.500 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg:
90.0 after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Flexibility:
Flexible
Color:
Black
Material:
Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpf-666, high voltage engineering corp
Material:
Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpf-666, high voltage engineering corp
Style Designator:
Transition-cross-shaped
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No