

View Online at <https://aerobasegroup.com/nsn/5970-01-149-8054>

Reliability Indicator:

Not established

Tempurature Rating:

248.0 degrees fahrenheit

Environmental Protection:

Flame resistant

Main Body Inside Diameter:

0.820 inches after unrestricted recovery

First Branch Inside Diameter:

0.820 inches after unrestricted recovery

Second Branch Inside Diameter:

0.820 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.620 inches after unrestricted recovery

Main Body Wall Thickness:

0.050 inches after unrestricted recovery

First Branch Wall Thickness:

0.050 inches after unrestricted recovery

Second Branch Wall Thickness:

0.050 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.480 inches after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

45.0 after unrestricted recovery

End Application:

Used on ifv xm2

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Plastic, elastomeric polymer blend, rt-1321, raychem corp

Material:

Plastic, elastomeric polymer blend, rt-1321, raychem corp

Style Designator:

Transition-y

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500