Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-153-0895

view online at https://delobdsegroup.com/hs/woord of 100 0000
Tempurature Rating:
-55.0 degrees celsius and 225.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Inside Diameter:
1.060 inches as supplied
First Branch Inside Diameter:
0.520 inches as supplied
Distance From Intersecting Centerline Of Main Body To End Of First Branch:
2.110 inches after unrestricted recovery
Main Body Wall Thickness:
0.100 inches after unrestricted recovery
First Branch Wall Thickness:
0.060 inches after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines:
2.750 inches after unrestricted recovery
Main Bodylength:
5.700 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg:
45.0 after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Flexibility:
Flexible
Color:
Black
Material:
Plastic, flex poly, rt-1304, raychem corp
Material:
Plastic, flex poly, rt-1304, raychem corp
Style Designator:
Transition-45 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A22500