Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-154-6859

## **Tempurature Rating:** -55.0 degrees celsius and 135.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and water resistant Main Body Wall Thickness: 0.080 inches after unrestricted recovery Main Bodylength: 1.830 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.220 inches as supplied Main Body Large End Inside Diameter: 1.220 inches as supplied Distance From Bottom Of Shoulder To Large End Of Main Body: 0.590 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.700 inches after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch **Special Features:** Large end has lip; molding ports included Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, mil-i-81765/1, type 2 or plastic polyolefin, rt-1304, raychem corp Material: Plastic, polyolefin, mil-i-81765/1, type 2 or plastic polyolefin, rt-1304, raychem corp Style Designator: Boot-straight **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A22500