## NSN 5970-01-154-6859

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-154-6859

| _ |      |      |       | _    |       |    |
|---|------|------|-------|------|-------|----|
| Т | am   | niii | ratii | ro R | ≀atin | u. |
|   | CIII | vui  | atu   | 161  | \auii | ч. |

-55.0 degrees celsius and 135.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and water resistant

## Main Body Wall Thickness:

0.080 inches after unrestricted recovery

#### Main Bodylength:

1.830 inches after unrestricted recovery

## Main Body Small End Inside Diameter:

1.220 inches as supplied

#### Main Body Large End Inside Diameter:

1.220 inches as supplied

#### Distance From Bottom Of Shoulder To Large End Of Main Body:

0.590 inches after unrestricted recovery

#### Distance From Top Of Shoulder To Small End Of Main Body:

0.700 inches after unrestricted recovery

## Min. Tensile Strength (psi):

1200 pounds per square inch

#### **Special Features:**

Large end has lip; molding ports included

## Flexibility:

Semirigid

# Color:

Black

#### Material:

Plastic, polyolefin, mil-i-81765/1, type 2 or plastic polyolefin, rt-1304, raychem corp

## Material:

Plastic, polyolefin, mil-i-81765/1, type 2 or plastic polyolefin, rt-1304, raychem corp

#### **Style Designator:**

Boot-straight

## **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

## Shelf Life:

N/a

#### **Unit Of Measure:**

## **Demilitarization:**

No

## Fiig:

A22500