Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-158-4650

New Online at https://aeiobasegioup.com/nsi/3970-01-130-4030	
Reliability Indicator:	
Not established	
Tempurature Rating:	
-55.0 degrees celsius	
Environmental Protection:	
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant	
Distance From Centerline Of Main Body To End Of First Branch:	
1.160 inches after unrestricted recovery	
Main Body Inside Diameter:	
0.520 inches as supplied	
First Branch Inside Diameter:	
0.520 inches as supplied	
Main Body Wall Thickness:	
0.060 inches as supplied	
First Branch Wall Thickness:	
0.060 inches after unrestricted recovery	
Main Bodylength:	
2.310 inches after unrestricted recovery	
Angle Between Main Body And First Branch Centerlines In Deg:	
90.0 after unrestricted recovery	
Min. Tensile Strength (psi):	
1500 pounds per square inch	
Special Features:	
Inside coated w/adhesive	
Flexibility:	
Semirigid	
Color:	
Black	
Material:	
Plastic, polyolefin, rt-301, raychem corp	
Material:	
Plastic, polyolefin, rt-301, raychem corp	
Style Designator:	
Transition-t	
Dielectric Material Voltage Rating Per Unit Thickness:	
200.0 volts per military /0.001 inch/	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 5970-01-158-4650

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

