# NSN 5970-01-159-2649

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-159-2649

# **Tempurature Rating:**

-55.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

# **Main Body Inside Diameter:**

2.340 inches as supplied

#### First Branch Inside Diameter:

1.140 inches as supplied

# Distance From Intersecting Centerline Of Main Body To End Of First Branch:

3.660 inches after unrestricted recovery

#### Main Body Wall Thickness:

0.180 inches after unrestricted recovery

#### First Branch Wall Thickness:

0.100 inches after unrestricted recovery

#### **Distance From Edge Of Main Body To Intersecting Centerlines:**

3.760 inches after unrestricted recovery

#### Main Bodylength:

8.010 inches after unrestricted recovery

# Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

# Min. Tensile Strength (psi):

1500 pounds per square inch

#### **Special Features:**

Inside adhesive coated

# Flexibility:

Semirigid

# Color:

Black

#### Material:

Plastic, polyolefin, rt-301, raychem corp

#### Material:

Plastic, polyolefin, rt-301, raychem corp

# **Style Designator:**

Transition-45 degrees

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# Shelf Life:

N/a

# **Unit Of Measure:**

--

#### **Demilitarization:**

No

# NSN 5970-01-159-2649

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500