NSN 5970-01-162-2680

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-162-2680
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Wall Thickness:
0.130 inches after unrestricted recovery
Main Bodylength:
5.130 inches after unrestricted recovery
Main Body Small End Inside Diameter:
2.040 inches as supplied
Main Body Large End Inside Diameter:
2.040 inches as supplied
Distance From Bottom Of Shoulder To Large End Of Main Body:
2.540 inches after unrestricted recovery
Distance From Top Of Shoulder To Small End Of Main Body:
1.560 inches after unrestricted recovery
Min. Tensile Strength (psi):
1500 pounds per square inch
Special Features:
Large end has lip; inside adhesive coated
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co
Material:
Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co
Style Designator:
Boot-straight
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

No

Fiig:

A22500