NSN 5970-01-163-1569

Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-163-1569

| Overall Length: |
|---|
| 4.000 feet |
| Tempurature Rating: |
| -55.0 degrees celsius and 135.0 degrees celsius |
| Environmental Protection: |
| Chemical resistant and corrosion resistant and flame resistant and mildew resistant |
| Expanded Inside Diameter: |
| 2.4 millimeters |
| Recovered Inside Diameter: |
| 1.2 millimeters |
| Recovered Wall Thickness: |
| 0.5 millimeters |
| Heat Shrinkage Rating In Percent: |
| 50.0 |
| Min. Tensile Strength (psi): |
| 2500 pounds per square inch |
| Flexibility: |
| Semirigid |
| Color: |
| Black |
| Material: |
| Plastic, polyolefin, rt-360, type 1, raychem corp |
| Material: |
| Plastic polyolefin |
| Style Designator: |
| Shrinkable |
| Test Data Document: |
| 06090-rt-360 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Dielectric Material Voltage Rating Per Unit Thickness: |
| 800.0 volts per military /0.001 inch/ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A22500 |