NSN 5970-01-163-5191

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-163-5191

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Large End Wall Thickness Of Main Body:

0.030 inches after unrestricted recovery and 0.120 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.060 inches after unrestricted recovery

Main Bodylength:

4.140 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.680 inches as supplied

Main Body Large End Inside Diameter:

0.940 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

3.450 inches after unrestricted recovery

End Largest Diameter:

Any acceptable as supplied

Min. Tensile Strength (psi):

1500 pounds per square inch

Lip Height:

0.060 inches after unrestricted recovery

Lip Width:

0.050 inches after unrestricted recovery

Flexibility:

Flexible

Height:

0.730 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin, rt-1316, raychem corp

Material:

Plastic, polyolefin, rt-1316, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5970-01-163-5191

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500