Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-168-0657

<b>Reliability Indica</b>	ator:
Not established	
Overall Length:	
Any acceptable	
Tempurature Ra	iting:
-67.0 degrees ce	Isius and 250.0 degrees celsius
Environmental F	Protection:
Corrosion resista	nt and flame resistant and mildew resistant and water resistant
Expanded Inside	e Diameter:
0.065 inches	
Recovered Insid	le Diameter:
0.043 inches	
Recovered Wall	Thickness:
Between 0.009 ir	nches and 0.015 inches
Heat Shrinkage	Rating In Percent:
33.9	
Min. Tensile Stro	ength (psi):
2500 pounds per	square inch
Flexibility:	
Flexible	
Color:	
Clear	
Material:	
Plastic, polytetraf	fluoroethylene, mil-i-23053/12, class 3
Material:	
Plastic polytetrafl	uoroethylene
Style Designato	r:
Shrinkable	
Dielectric Mater	ial Voltage Rating Per Unit Thickness:
800.0 volts per m	ilitary /0.001 inch/
Shelf Life:	
N/a	
Unit Of Measure	
Demilitarization	:
No	
Fiig:	
A22500	