

View Online at <https://aerobasegroup.com/nsn/5970-01-173-1846>

**Tempurature Rating:**

120.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and mildew resistant

**Main Body Inside Diameter:**

0.520 inches as supplied

**First Branch Inside Diameter:**

0.260 inches as supplied

**Second Branch Inside Diameter:**

0.260 inches as supplied

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

0.760 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.060 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.040 inches after unrestricted recovery

**Second Branch Wall Thickness:**

0.040 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:**

0.880 inches after unrestricted recovery

**Angle Between Main Body And Second Branch Centerlines In Deg:**

22.5 after unrestricted recovery

**End Application:**

Mrap - common nsn - used on maxxpro cat i and 4 other weapon systems

**Min. Tensile Strength (psi):**

2800 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Plastic, vinyl, mil-i-7444

**Material:**

Plastic, vinyl, mil-i-7444

**Style Designator:**

Transition-y

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500