## NSN 5970-01-173-1846

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-173-1846
Tempurature Rating:
120.0 degrees celsius
Environmental Protection:
Corrosion resistant and mildew resistant
Main Body Inside Diameter:
0.520 inches as supplied
First Branch Inside Diameter:
0.260 inches as supplied
Second Branch Inside Diameter:
0.260 inches as supplied
Distance From Intersecting Centerline Of Main Body To End Of First Branch:
0.760 inches after unrestricted recovery
Main Body Wall Thickness:
0.060 inches after unrestricted recovery
First Branch Wall Thickness:
0.040 inches after unrestricted recovery
Second Branch Wall Thickness:
0.040 inches after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines:
0.880 inches after unrestricted recovery
Angle Between Main Body And Second Branch Centerlines In Deg:
22.5 after unrestricted recovery
End Application:
Mrap - common nsn - used on maxxpro cat i and 4 other weapon systems
Min. Tensile Strength (psi):
2800 pounds per square inch
Flexibility:
Flexible
Color:
Black
Material:
Plastic, vinyl, mil-i-7444
Material:
Plastic, vinyl, mil-i-7444
Style Designator:
Transition-y
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5970-01-173-1846

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500