

View Online at <https://aerobasegroup.com/nsn/5970-01-179-2962>

Tempurature Rating:

-55.0 degrees celsius and 125.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant

Main Body Inside Diameter:

1.770 inches after unrestricted recovery

First Branch Inside Diameter:

0.810 inches as supplied

Second Branch Inside Diameter:

0.810 inches as supplied

Third Branch Inside Diameter:

0.810 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

2.670 inches after unrestricted recovery

Main Body Wall Thickness:

0.050 inches after unrestricted recovery

First Branch Wall Thickness:

0.050 inches after unrestricted recovery

Second Branch Wall Thickness:

0.050 inches after unrestricted recovery

Third Branch Wall Thickness:

0.050 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.670 inches after unrestricted recovery

Main Bodylength:

5.340 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

Any acceptable as supplied

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Plastic, elastomeric polymer blend, rt-1321, raychem corp

Material:

Plastic, elastomeric polymer blend, rt-1321, raychem corp

Style Designator:

Transition-1 to 3 cables

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500