# NSN 5970-01-180-0809

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-180-0809

# **Tempurature Rating:**

-55.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

# Large End Wall Thickness Of Main Body:

0.150 inches after unrestricted recovery

#### Small End Wall Thickness Of Main Body:

0.150 inches after unrestricted recovery

#### **Distance From Intersecting Centerlines To Edge Of Small End:**

3.840 inches after unrestricted recovery

#### Distance From Centerline Of Small End To Edge Of Large End:

Any acceptable as supplied

#### Main Body Small End Inside Diameter:

2.100 inches as supplied

#### Main Body Large End Inside Diameter:

1.770 inches as supplied

# Distance From Top Of Shoulder To Small End Of Main Body:

1.600 inches after unrestricted recovery

# Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

# Min. Tensile Strength (psi):

1500 pounds per square inch

#### **Special Features:**

Large end threaded with nut

# Flexibility:

Semirigid

# Height:

Any acceptable as supplied

#### Color:

Black

#### Material:

Plastic, polyolefin, rt-301, raychem corp

#### Material:

Plastic, polyolefin, rt-301, raychem corp

# **Style Designator:**

Boot-90 degrees

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5970-01-180-0809

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500