NSN 5970-01-181-6211

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-181-6211

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

2.050 inches as supplied

First Branch Inside Diameter:

1.060 inches as supplied

Second Branch Inside Diameter:

1.060 inches as supplied

Third Branch Inside Diameter:

1.060 inches as supplied

Fourth Branch Inside Diameter:

1.060 inches as supplied

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.100 inches after unrestricted recovery

Second Branch Wall Thickness:

0.100 inches after unrestricted recovery

Third Branch Wall Thickness:

0.100 inches after unrestricted recovery

Fourth Branch Wall Thickness:

0.100 inches after unrestricted recovery

Main Bodylength:

4.250 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Inside coated with s-1017 adhesive

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corp

Material:

Plastic, polyolefin, rt-301, raychem corp

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

NSN 5970-01-181-6211

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A22500