NSN 5970-01-181-8237

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-181-8237

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

1.200 inches as supplied

First Branch Inside Diameter:

0.500 inches as supplied

Second Branch Inside Diameter:

0.500 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.920 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.050 inches after unrestricted recovery

Second Branch Wall Thickness:

0.050 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.680 inches after unrestricted recovery

Main Bodylength:

3.230 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Inside coated with adhesive

Flexibility:

.

Semirigid

Color: Black

Material:

Plastic, polyolefin, rt-301, raychem corp

Material:

Plastic, polyolefin, rt-301, raychem corp

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5970-01-181-8237

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500