Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-183-8663

No established Overall Length: Any acceptable Tempurature Rating: -70.0 degrees celsius and 121.0 degrees celsius Environmental Protection: Corrosion resistant and flame resistant and mildew resistant and water resistant Expanded Inside Diameter: 1.000 inches Recovered Inside Diameter: 1.000 inches Recovered Inside Diameter: 1.000 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Sheff Life: Na	Peliability Indicator:	
Overall Length: Any acceptable Tempurature Rating: -70.0 degrees celsius and 121.0 degrees celsius Environmental Protection: Corrosion resistant and flame resistant and mildew resistant and water resistant Expanded Inside Diameter: 1.000 inches Recovered Inside Diameter: 0.570 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Piexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Reliability Indicator:	
Any acceptable Tempurature Rating: -70.0 degrees celsius and 121.0 degrees celsius Environmental Protection: Corrosion resistant and flame resistant and mildew resistant and water resistant Expanded Inside Diameter: 1.000 inches Recovered Inside Diameter: 0.570 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibilty: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Sheff Life: N/a		
Tempurature Rating: -70.0 degrees celsius and 121.0 degrees celsius Environmental Protection: Corrosion resistant and flame resistant and mildew resistant and water resistant Expanded Inside Diameter: 1.000 inches Recovered Inside Diameter: 0.570 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a		
-70.0 degrees celsius and 121.0 degrees celsius Environmental Protection: Corrosion resistant and flame resistant and mildew resistant and water resistant Expanded Inside Diameter: 1.000 inches Recovered Inside Diameter: 0.570 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a		
Environmental Protection: Corrosion resistant and flame resistant and mildew resistant and water resistant Expanded Inside Diameter: 1.000 inches Recovered Inside Diameter: 0.570 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Vottage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a		
Corrosion resistant and flame resistant and mildew resistant and water resistant Expanded Inside Diameter: 1.000 inches Recovered Inside Diameter: 0.570 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a		
Expanded Inside Diameter: 1.000 inches Recovered Inside Diameter: 0.570 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a		
1.000 inches Recovered Inside Diameter: 0.570 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a		
Recovered Inside Diameter: 0.570 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 143.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	-	
0.570 inches Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexibile Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a		
Recovered Wall Thickness: Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a		
Between 0.050 inches and 0.090 inches Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	0.570 inches	
Heat Shrinkage Rating In Percent: 43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Recovered Wall Thickness:	
43.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Between 0.050 inches and 0.090 inches	
Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Heat Shrinkage Rating In Percent:	
1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	43.0	
Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Min. Tensile Strength (psi):	
Flexible Flexible Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	1500 pounds per square inch	
Color: Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life:	Flexibility:	
Black Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Flexible	
Material: Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Color:	
Rubber, neoprene, rt-511, raychem corp Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Black	
Material: Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Material:	
Rubber Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Rubber, neoprene, rt-511, raychem corp	
Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Material:	
Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Rubber	
Dielectric Material Voltage Rating Per Unit Thickness: 300.0 volts per military /0.001 inch/ Shelf Life: N/a	Style Designator:	
300.0 volts per military /0.001 inch/ Shelf Life: N/a	Shrinkable	
Shelf Life: N/a	Dielectric Material Voltage Rating Per Unit Thickness:	
N/a	300.0 volts per military /0.001 inch/	
	Shelf Life:	
Unit Of Measure:	N/a	
	Unit Of Measure:	
Demilitarization:	Demilitarization:	
No	No	
Fiig:	Fiig:	
A22500	A22500	