Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-185-3775

Tempurature Rating: -40.0 degrees celsius and 300.0 degrees celsius **Environmental Protection:** Flame resistant and mildew resistant and water resistant Main Body Wall Thickness: 0.070 inches after unrestricted recovery Main Bodylength: 2.900 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.710 inches as supplied Main Body Large End Inside Diameter: 1.180 inches as supplied Distance From Bottom Of Shoulder To Large End Of Main Body: 1.630 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.870 inches after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, fluoroelastomer, mil-i-23053/13 or rubber, fluoroelastomer, viton rt-1146, raychem inc Material: Rubber, fluoroelastomer, mil-i-23053/13 or rubber, fluoroelastomer, viton rt-1146, raychem inc Style Designator: Boot-straight **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A22500