

View Online at <https://aerobasegroup.com/nsn/5970-01-190-2542>

**Tempurature Rating:**

-55.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

**Large End Wall Thickness Of Main Body:**

0.150 inches after unrestricted recovery

**Small End Wall Thickness Of Main Body:**

0.150 inches after unrestricted recovery

**Distance From Intersecting Centerlines To Edge Of Small End:**

3.840 inches after unrestricted recovery

**Distance From Centerline Of Small End To Edge Of Large End:**

1.640 inches after unrestricted recovery

**Main Body Small End Inside Diameter:**

2.600 inches as supplied

**Main Body Large End Inside Diameter:**

2.600 inches as supplied

**Distance From Top Of Shoulder To Small End Of Main Body:**

1.580 inches after unrestricted recovery

**Angle Between Large End And Small End Centerlines In Deg:**

90.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Special Features:**

Large end has lip

**Flexibility:**

Semirigid

**Height:**

2.600 inches after unrestricted recovery

**Color:**

Black

**Material:**

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mil-i-81765/1, type i

**Material:**

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mil-i-81765/1, type i

**Style Designator:**

Boot-90 degrees

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500