Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-190-2542

view Online at https://aerobasegroup.com/hsn/5970-01-190-2542	
Tempurature Rating:	
-55.0 degrees celsius	
Environmental Protection:	
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant	
Large End Wall Thickness Of Main Body:	
0.150 inches after unrestricted recovery	
Small End Wall Thickness Of Main Body:	
0.150 inches after unrestricted recovery	
Distance From Intersecting Centerlines To Edge Of Small End:	
3.840 inches after unrestricted recovery	
Distance From Centerline Of Small End To Edge Of Large End:	
1.640 inches after unrestricted recovery	
Main Body Small End Inside Diameter:	
2.600 inches as supplied	
Main Body Large End Inside Diameter:	
2.600 inches as supplied	
Distance From Top Of Shoulder To Small End Of Main Body:	
1.580 inches after unrestricted recovery	
Angle Between Large End And Small End Centerlines In Deg:	
90.0 after unrestricted recovery	
Min. Tensile Strength (psi):	
1500 pounds per square inch	
Special Features:	
Large end has lip	
Flexibility:	
Semirigid	
Height:	
2.600 inches after unrestricted recovery	
Color:	
Black	
Material:	
Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mil-i-81765/1, type i	
Material:	
Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mil-i-81765/1, type i	
Style Designator:	
Boot-90 degrees	
Dielectric Material Voltage Rating Per Unit Thickness:	
200.0 volts per military /0.001 inch/	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5970-01-190-2542

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500