Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-199-9101

Tempurature Rating:
-55.0 degrees celsius and 135.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant
Main Body Inside Diameter:
1.200 inches as supplied
First Branch Inside Diameter:
0.500 inches as supplied
Second Branch Inside Diameter:
0.500 inches as supplied
Distance From Intersecting Centerline Of Main Body To End Of First Branch:
2.000 inches after unrestricted recovery
Main Body Wall Thickness:
0.100 inches after unrestricted recovery
First Branch Wall Thickness:
0.050 inches after unrestricted recovery
Second Branch Wall Thickness:
0.050 inches after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines:
1.750 inches after unrestricted recovery
Main Bodylength:
3.500 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg:
30.0 after unrestricted recovery
Min. Tensile Strength (psi):
2175 pounds per square inch
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, elastomer, rt-1325, raychem corp
Material:
Plastic, elastomer, rt-1325, raychem corp
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5970-01-199-9101

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

