NSN 5970-01-200-0856

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-200-0856

Tempurature Rating:

-75.0 degrees celsius and 150.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant

Main Body Inside Diameter:

1.200 inches as supplied

First Branch Inside Diameter:

0.800 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

2.000 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches as supplied

First Branch Wall Thickness:

0.070 inches as supplied

Distance From Edge Of Main Body To Intersecting Centerlines:

1.250 inches after unrestricted recovery

Main Bodylength:

3.250 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

30.0 after unrestricted recovery

Min. Tensile Strength (psi):

2175 pounds per square inch

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, elastomeric, rt-1325, raychem corp

Material:

Plastic, elastomeric, rt-1325, raychem corp

Style Designator:

Transition-45 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500