Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-203-7646

Tempurature Rating: -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Distance From Intersecting Centerlines To Edge Of Small End: 1.210 inches after unrestricted recovery Distance From Centerline Of Small End To Edge Of Large End: 0.730 inches after unrestricted recovery Main Body Wall Thickness: 0.040 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.750 inches as supplied Main Body Large End Inside Diameter: 1.110 inches after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch **Special Features:** Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, polyolefin, mil-i-81765/1, type ii or plastic, polyolefin, rt-1304, raychem corp Material: Plastic, polyolefin, mil-i-81765/1, type ii or plastic, polyolefin, rt-1304, raychem corp Style Designator: Boot-rectangular-90 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A22500