Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-210-3273

view Online at https://aerobasegroup.com/hsn/5970-01-210-5275
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Wall Thickness:
0.060 inches after unrestricted recovery
Main Bodylength:
4.170 inches after unrestricted recovery
Main Body Small End Inside Diameter:
0.880 inches as supplied
Main Body Large End Inside Diameter:
0.880 inches as supplied
Distance From Bottom Of Shoulder To Large End Of Main Body:
0.460 inches after unrestricted recovery
End Application:
Mrap rg-33
Min. Tensile Strength (psi):
1200 pounds per square inch
Special Features:
Large end has lip; wall thk tapers from large end of main body to 0.045 in. Small end
Flexibility:
Flexible
Color:
Black
Material:
Plastic, polyolefin, rt-1304, raychem corp
Material:
Plastic, polyolefin, rt-1304, raychem corp
Style Designator:
Boot-straight-long
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A22500