NSN 5970-01-213-5138

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-213-5138

Reliability Indicator:

Not established

Main Body Inside Diameter:

2.370 inches after unrestricted recovery

First Branch Inside Diameter:

1.420 inches after unrestricted recovery

Second Branch Inside Diameter:

1.420 inches after unrestricted recovery

Third Branch Inside Diameter:

1.420 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

2.670 inches after unrestricted recovery

Main Body Wall Thickness:

0.060 inches after unrestricted recovery

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Second Branch Wall Thickness:

0.060 inches after unrestricted recovery

Third Branch Wall Thickness:

0.060 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.670 inches after unrestricted recovery

Main Bodylength:

5.340 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

End Application:

Mrap - cougar cat1 a1

Flexibility:

Flexible

Color:

Tan

Material:

Plastic, vinyl chloride polymer

Material:

Plastic polyvinyl chloride

Style Designator:

Transition-1 to 3 cables

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5970-01-213-5138

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500