

View Online at <https://aerobasegroup.com/nsn/5970-01-213-6168>

**Tempurature Rating:**

-55.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

**Main Body Inside Diameter:**

2.190 inches as supplied

**First Branch Inside Diameter:**

0.520 inches as supplied

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

2.360 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.180 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.060 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:**

3.280 inches after unrestricted recovery

**Main Bodylength:**

6.320 inches as supplied

**Angle Between Main Body And First Branch Centerlines In Deg:**

45.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Special Features:**

Main body id tapers to 1.060 in. Min as supplied, 0.490 in. Maximum after recovery; main body wall thk tapers to 0.100 in. Maximum as supplied, 0.100 in. after recovery

**Flexibility:**

Semirigid

**Color:**

Black

**Material:**

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mil-i-23053/5

**Material:**

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mil-i-23053/5

**Style Designator:**

Transition-45 degrees

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500