Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-213-7417

Tempurature Rating: -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and water resistant Distance From Centerline Of Main Body To End Of First Branch: 1.000 inches after unrestricted recovery Main Body Inside Diameter: 1.400 inches as supplied **First Branch Inside Diameter:** 0.600 inches as supplied Main Body Wall Thickness: 0.100 inches after unrestricted recovery **First Branch Wall Thickness:** 0.060 inches after unrestricted recovery Main Bodylength: 2.000 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Includes molding ports Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp Style Designator: Transition-t **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A22500