NSN 5970-01-216-0010

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-216-0010

_				_		
Т	am	niii	ratii	ro R	≀atin	u.
	CIII	vui	atu	161	\auii	ч.

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Main Body Wall Thickness:

0.060 inches after unrestricted recovery

Main Bodylength:

2.370 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.250 inches as supplied

Main Body Large End Inside Diameter:

0.760 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

0.460 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

White color stripe; large end has lip; includes drain holes; small end wall thk 0.045 in.

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, minnesota mining and mfg co

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, minnesota mining and mfg co

Style Designator:

Boot-straight-long

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500