# NSN 5970-01-217-4148

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-217-4148

Tom	nuratur	e Rating	
ı em	puratur	e Kating	-

-55.0 degrees celsius

## **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

## Large End Wall Thickness Of Main Body:

0.090 inches after unrestricted recovery

## Small End Wall Thickness Of Main Body:

0.040 inches after unrestricted recovery

## Distance From Intersecting Centerlines To Edge Of Small End:

1.870 inches after unrestricted recovery

## Main Body Small End Inside Diameter:

0.970 inches as supplied

## Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

## Min. Tensile Strength (psi):

1500 pounds per square inch

## **Special Features:**

Inside surface coated with adhesive; one jack screw hole

## Flexibility:

Semirigid

## Color:

Black

## Material:

Plastic, polyolefin, rt-301, raychem corp

## Material:

Plastic, polyolefin, rt-301, raychem corp

## **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

## Shelf Life:

N/a

## **Unit Of Measure:**

--

## Demilitarization:

No

## Fiig:

A22500