NSN 5970-01-218-6697

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-218-6697

ı em	purature	Naumu.

-55.0 degrees celsius and 225.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Wall Thickness:

0.080 inches after unrestricted recovery

Main Bodylength:

3.900 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.680 inches as supplied

Main Body Large End Inside Diameter:

1.680 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

2.470 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

0.710 inches after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Special Features:

Inside coated with adhesive

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpp-262, 3m co

Material:

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpp-262, 3m co

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

225.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500