Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-218-6697

Tempurature Rating:
-55.0 degrees celsius and 225.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Wall Thickness:
0.080 inches after unrestricted recovery
Main Bodylength:
3.900 inches after unrestricted recovery
Main Body Small End Inside Diameter:
1.680 inches as supplied
Main Body Large End Inside Diameter:
1.680 inches as supplied
Distance From Bottom Of Shoulder To Large End Of Main Body:
2.470 inches after unrestricted recovery
Distance From Top Of Shoulder To Small End Of Main Body:
0.710 inches after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Special Features:
Inside coated with adhesive
Flexibility:
Flexible
Color:
Black
Material:
Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpp-262, 3m co
Material:
Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpp-262, 3m co
Style Designator:
Boot-straight
Dielectric Material Voltage Rating Per Unit Thickness:
225.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A22500