Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-226-6492

| Tempurature R | ating: |
|-------------------|--|
| -55.0 degrees ce | elsius and 225.0 degrees celsius |
| Environmental | Protection: |
| Corrosion resista | ant and flame resistant and mildew resistant and solvent resistant and water resistant |
| Main Body Wal | I Thickness: |
| 0.070 inches af | ter unrestricted recovery |
| Main Bodyleng | th: |
| 2.020 inches af | ter unrestricted recovery |
| Main Body Sma | all End Inside Diameter: |
| 1.120 inches as | supplied |
| Main Body Larg | ge End Inside Diameter: |
| 1.120 inches as | supplied |
| Distance From | Bottom Of Shoulder To Large End Of Main Body: |
| 1.100 inches af | ter unrestricted recovery |
| Distance From | Top Of Shoulder To Small End Of Main Body: |
| 0.510 inches af | ter unrestricted recovery |
| Min. Tensile St | rength (psi): |
| 1500 pounds pe | r square inch |
| Special Feature | 25: |
| With molding po | rts; inside adhesive coated |
| Flexibility: | |
| Flexible | |
| Color: | |
| Black | |
| Material: | |
| Plastic, polyolef | in, rt-301, raychem corporation or plastic, polyolefin, mpp-262, minnesota mining and mfg co |
| Material: | |
| Plastic, polyolef | in, rt-301, raychem corporation or plastic, polyolefin, mpp-262, minnesota mining and mfg co |
| Style Designate | Dr: |
| Boot-straight | |
| Dielectric Mate | rial Voltage Rating Per Unit Thickness: |
| 200.0 volts per r | nilitary /0.001 inch/ |
| Shelf Life: | |
| N/a | |
| Unit Of Measur | e: |
| | |
| Demilitarizatior | 1: |
| No | |
| Fiig: | |
| A22500 | |